


Mhor 1:500
Mvert 1:50


39.50
39.00
38.50
38.00
37.50
37.00

K1V-1 Väijund H=1.22
K1-1 400/315 H=1.25
KLP 200/160 H=1.43

1

V1S-1 H=1.83
V11-1 H=2.10
VLP H=1.83
Sisend
Veemöödukaev
Maakraan DN25

KAEVU/SÕLME NR	K1-1		KLP	V1S-1	V11-1 VLP	
OLEMASOLEVA MAAPINNA KÕRGUS (m abs)	39.80	39.80	39.60	39.80	39.60	39.60
PROJEKTEERITUD MAAPINNA KÕRGUS (m abs)	39.80	39.80	39.60	39.80	39.60	39.60
TORU PÕHJA KÕRGUS (m abs)	38.58	38.55	38.22	38.00	37.80	37.80
TORU RAJAMISSÜGAVUS (m)	1.22	1.25	1.38	1.83	1.83	1.83
KALLE	24.0		0.0150	21.4	0.0094	0.0000
PIKKUS (m)					3.8	
TORU LÄBIMÕÖT (mm) JA MATERJAL	De110 - 24.0m			De32 - 25.2m		
VAHEKAUGUSED (m)	2.1	22.0		2.7	21.4 16.6	3.8 1.5 2.4
SIRGESTATUD TRASSI PLAAN						

Kaevu tähis	Kogus	Tüüp	Kaevu läbimõõt [mm]	Kaevu materjal	Kaevu kõrgus [m]	Kaevu sügavus vv-st [m]
K1-1	1	K1	400	400/315	1.25	0.00
		Nr	Trassi läbimõõt [mm]	Trassi materjal	Nurk	Trassi kõrgus vv-st [m]
		1	110.00	De110	0°	0.00
		2	110.00	De110	90°	0.00