



Katus	KK - 1
( - )	
Profiilplekk	
Aluslaudis 25x100	25 mm
Tuulutusroov 25x50	25 mm
Aluskate	0.5 mm
Sarikas/ferm	
( - )	

Vahelagi	VL - 1
U=0.07 W/m²K	515 mm
( - )	
Tala/ferm	45x145
/ Min.puistevill	400mm
soojuseri juhtivus λ <sub>0</sub> =0.041 W/mk	
Aurutõke PE-kile	0.2 mm
Laudis 25x75	25 mm
Roovid 45x45	45 mm
Roovid 28x70	28 mm
Kipsplaat	12 mm
( + )	

Vahelagi	VL - 1
( + )	360 mm
Põrandakate	
RB-plaat	80 mm
Minu.vill Isover FLO	50 mm
RB-õõnespaneel	220 mm
( + )	

Põrand pinnasel	PP - 1
U=0.115 W/m²K	
( + )	
Põrandakate	...20 mm
RB-plaat	100 mm
Eralduskiht, PE-kile	0.2 mm
EPS 120	300 mm
Tihendatud liiv	300 mm
( - )	
Põrand pinnasel	PP - 2
U=0.125 W/m²K	
( + )	
RB-plaat	150 mm
Eralduskiht, PE-kile	0.2 mm
EPS 120	200 mm
Tihendatud liiv	300 mm
( - )	

Välissein	VS - 21
U=0.160 W/m²K	445 mm
( - )	
Krohv	12 mm
Roov, teras tuulutav	28 mm
Min.vill Isover RKL	30 mm
soojuseri juhtivus λ <sub>0</sub> =0.031 W/mk	
Poorbet. plokk	375 mm
Siseviimistlus	
( + )	

Välissein	VS - 11
U=0.160 W/m²K	435 mm
( - )	
Krohv	10 mm
Min.vill Isover FS5	50 mm
soojuseri juhtivus λ <sub>0</sub> =0.035 W/mk	
Poorbet. plokk	375 mm
Siseviimistlus	
( + )	

Soklisein	VS - 01
U=0.150 W/m²K	410 mm
( - )	
Krohv	10 mm
EPS 120 perimeeter	150 mm
FIBO plokk	200 mm
( - )	