


24 92 07




Transition coupler PE/steel (stainless 1.4305) Male thread

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Delivered as a kit. Further combinations: modular system with threaded adapter and reductions

d [mm]	R [inch]	Code	GP	kg	d1 [mm]	L [mm]	s [mm]
20	1/2	724 920 756	6	0.165	31	110	30
25	3/4	724 920 757	6	0.249	36	111	35
32	1	724 920 758	6	0.332	44	117	40
40	1 1/4	724 920 759	6	0.464	54	127	50
40	1 1/2	724 920 772	6	0.528	66	143	60
50	1 1/2	724 920 760	6	0.611	66	135	60
63	1 1/2	724 920 771	3	0.904	81	147	70
63	2	724 920 761	3	0.942	81	147	70

PF 2 51 314 004

24 92 02




Transition coupler PE/steel (stainless 1.4305) Female thread

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit

d [mm]	Rp [inch]	Code	GP	kg	d1 [mm]	L [mm]	s [mm]
20	1/2	724 920 256	6	0.179	31	100	30
25	3/4	724 920 257	6	0.231	36	101	35
32	1	724 920 258	6	0.319	44	108	40
40	1 1/4	724 920 259	6	0.480	54	118	50
50	1 1/2	724 920 260	6	0.646	66	126	60
63	2	724 920 261	3	0.931	81	138	70

PF 2 51 314 004

24 10 07



Transition elbow 90° PE/steel (stainless 1.4305) Male thread

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit

d [mm]	R [inch]	Code	GP	kg	d1 [mm]	L [mm]	s [mm]
20	1/2	724 100 756	6	0.211	31	96	30
25	3/4	724 100 757	6	0.230	36	97	35
32	1	724 100 758	6	0.324	44	98	40
40	1 1/4	724 100 759	6	0.560	54	109	50
40	1 1/2	724 100 772	6	0.599	54	109	60
50	1 1/2	724 100 760	6	0.701	66	118	60
63	1 1/2	724 100 771	3	0.986	81	132	70
63	2	724 100 761	3	1.105	81	132	70

PF 2 51 314 004