

Date: 19/11/2024

SSP Alias: B5T

PLATE HEAT EXCHANGER		Side 1	Side 2
Total heat transfer area	m ²		0.168
Heat flux	kW/m ²		39.3
Mean temperature difference	K		14.28
O.H.T.C. (available/required)	W/m ² , °C		3050/2750
Pressure drop - total*	kPa	0.271	11.3
- in ports	kPa	0.0168	1.18
Port diameter (up/down)	mm	16.0/16.0	16.0/16.0
Number of channels per pass		7	8
Number of plates			16
Oversurfacing	%		11
Fouling factor	m ² , °C/kW		0.034
Reynolds number		310.1	1578
Port velocity (up/down)	m/s	0.190/0.190	1.58/1.58
Channel velocity	m/s	0.0373	0.272
Shear stress	Pa	1.33	52.5
Average wall temperature	°C	42.85	41.77
Largest wall temperature difference	K		4.29
Min./Max. wall temperature	°C	35.88/51.75	35.56/47.47


*Excluding pressure drop in connections.

TOTALS		Side 1	Side 2
Total weight empty (no connections)*	kg		1.12 - 1.58
Total weight filled (no connections)*	kg		1.47 - 1.93
Hold-up volume (Inner Circuit)	dm ³		0.17
Hold-up volume (Outer Circuit)	dm ³		0.19
Port size F1/P1	mm		16
Port size F2/P2	mm		16
Port size F3/P3	mm		16
Port size F4/P4	mm		16
Carbon footprint	kg		8.43



*Weight depends on the selected product.

DIMENSIONS



A*	mm	192.8 - 193 ±2
B*	mm	75.4 - 76 ±2
C	mm	154 ±1
D	mm	40 ±1
E	mm	20 ±1
F*	mm	39.8 - 43.84 ±3%
G*	mm	6.2 - 7.4 ±2.1
R*	mm	17.7 - 18

*Dimensions depend on the selected product.

*This is a schematic sketch. For correct drawings please use the order drawing function or contact your SWEP representative.

Legal notice:

By using the SSP/DThermX software the Licensee confirms that the input data is not subject to export control laws including ITAR (International Traffic in Arms Regulations). Licensee further agrees and confirms that the configured products are not subject to export control laws including ITAR and do not qualify as "specially designed" for export control purposes. If you would like to discuss configuration of export controlled products including ITAR-qualifying products, or if your data is export controlled, please reach out to your SWEP representative or email info@swep.net.

Disclaimer:

Data used in this calculation is subject to change without notice. SWEP strives to use "best practice" for the calculations leading to the above results. Calculation is intended to show thermal and hydraulic performance, no consideration has been taken to mechanical strength of the product. Product restrictions - such as pressure, temperatures and corrosion resistance- can be found in SWEP product sheets and other technical documentation. SWEP may have patents, trademarks, copyrights or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from SWEP, the furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property. To the maximum extent permitted by applicable law, the software, the calculations and the results are provided without warranties of any kind, whether express or implied. No advice or information obtained through use of the software (including information provided in the results), will create any warranty not expressly stated in the applicable license terms. Without limiting the foregoing, SWEP does not warrant that the content (including the calculations and the results) is accurate, reliable or correct. SWEP does not warrant that any system comprising heat exchanger and other components, installed on the basis of calculations in this software, will meet your requirements or function to your satisfaction or expectations.

